

SPECIFICATION ACCORDING TO EN 649

CHARACTERISTICS	STANDARD	UNIT	Result
STRUCTURE			
Type of flooring	EN649	n/a	Solid vinyl plank
Construction	n/a	n/a	Heterogeneous
Edge finish	n/a	n/a	Square edge
Polyurethane reinforce	na	n/a	Yes PUR
SAFETY CRITERIA			
Fire resistance	ASTM E648	W/cm ²	≥ 0.45
Slip resistance	DIN51130	group	R8-R9
PERFORMANCE BEHAVIOR			
Size (Width x Length)	EN 427	mm	152.4 x 914.4 (Classic Collection) / 184.1 x 1219.2 (Antique Collection)
Coverage		m ²	3.34 (Classic Collection) / 3.37 (Antique Collection)
Packaging details	n/a	pcs	24 (Classic Collection) / 15 (Antique Collection)
Overall thickness	EN 428	mm	2.0
Squareness	ASTMF 2055	mm	< 0.10
Wear layer thickness	n/a	mm	0.20
Wear resistance	EN 660-2	group	T
Color fastness	ASTM 105-B02	rating	≥ 6
Thermal conductivity	EN 12524	W/mK	0.25
Stain and chemical resistance	ASTM 925	rating	Excellent
Residual indentation	ASTM F1914	%	≤ 0.10
Dimensional stability	ASTM F2199	%	MD ≤ 0.16 AMD ≤ 0.16
Castor chair ✓	Underfloor heating ✓		Antimicrobial and antifungal ✓
Antistatic behavior ✓	Chemical resistance ✓		

INSTALLATION

• **Job Condition**

Subfloor / underlayment shall be dry, clean and smooth. They shall be free from paint, varnish, solvents, wax, oil, existing adhesive residue or other foreign matter. Condition all flooring materials and adhesives to room temperature at least 48 hours prior to starting installation. Protect all materials from the direct flow of heat from hot-air registers, radiators, or other heating fixtures and appliances.

Note : It is highly recommended to have zero leveled sub-floor for installation of LVT/LVP. Please use self-leveling compound to level the sub-floor. IPS, vitrified/ceramic/mosaic tiles do not provide zero leveled floor.

• **Procedure**

Armstrong NATURAL CREATIONS must be installed using Arobond 44 Adhesive full spread. Rubber based or any solvent based adhesive should not be used in installing NATURAL CREATIONS.

MAINTENANCE

NATURAL CREATIONS is designed to be maintained by traditional resilient flooring maintenance methods. The urethane protective finish can make initial maintenance easier, as well as reduce ongoing maintenance procedures.

INITIAL MAINTENANCE IMMEDIATELY AFTER INSTALLATION

- Sweep or vacuum very thoroughly
- Damp mop with a dilute neutral detergent solution
- Do not wash the floor for at least four to five days after installation. Black marks and dirty spots can be treated by spot scrubbing (use nothing more abrasive than a 3M blue or green pad or equal)

WARRANTY

Armstrong warrants its regular (first quality) products to be free from manufacturing defects for **five (5) years** from the date of purchase.

Armstrong World Industries (India) Pvt. Ltd.

Boomerang, A-304, Chandivali Farm Road (near Chandivali Studio) Andheri (E), Mumbai - 400 072
Tel: 022-3048 0800, Fax: 022-3046 0439 / 2491 3604 | e-mail : helpdeskindia@armstrong.com

Branches:

Ahmedabad : +91-85111 46309	Bangalore : +91-80-2657 6367	Chandigarh : +91-172-2633 680
Chennai : +91-44-4217 5303	Gurgaon : +91-93126 73142	Hyderabad : +91-40-3200 9868
Pune : +91-20-3250 2404	Kolkata : +91-33-2401 4755	Lucknow : +91-522-220 1143

Representatives:

Delhi/NCR : +91-93126 73147	Mumbai : +91-75066 73538	Bangalore : +91-77609 75976
: +91-93126 73148	: +91-75066 73539	: +91-96861 33161
Kolkata : +91-99030 81018	Ahmedabad : +91-85111 46309	Bhopal : +91-97543 17414
: +91-99039 20499		
Chandigarh : +91-99888 77683	Chennai : +91-93677 81490	Cochin : +91-99477 87111
Hyderabad : +91-77998 89881	Jaipur : +91-93525 69512	Lucknow : +91-99363 42422
Pune : +91-84110 02915		

LUXURY VINYL PLANKS

Natural Creations



ArborArt-Wood



Classic Oak
ACP429120



Pecan
ACP429420



Honey Beech
ACP411620



Oak Natural
ACP241420



Light Oak
ACP000420



Dark Walnut
ACP456120C



Dark Oak
ACP000320



Jatoba
ACP429520

Classic

6"x36" (152.4x914.4x2.0mm)

ArborArt-Wood



Knotty Oak
AAP408320



Milled Oak Light
AAP241620



Rustik Gray
AAP4245H20



Oak Medium
AAP4081C20



Weathered Oak
AAP241720



American Dark Oak
AAP489420



Milled Oak
AAP240220



Antique Wood Medium
AAP003120

Antique

7.25"x48" (184.1x1219.2x2.0mm)

*0.20mm wear layer for Residential applications - available in stock
** 0.30mm and 0.50mm wear layer for Residential and Commercial application - available upon request

*0.20mm wear layer for Residential applications - available in stock
** 0.30mm and 0.50mm wear layer for Residential and Commercial application - available upon request